



## Fatigue-Step

Fatigue relief for large shop floor areas



- Tiles link together to provide an anti-fatigue surface for particularly wet or oily areas.
- Soft, yet resilient rubber floor tiles.
- Open holes allow efficient drainage of spilt liquids.
- Effective anti-fatigue properties for prolonged standing.
- Slip tested to DIN 51130.
- Optional ramped edging in yellow or black.



## Parts

Part Number	Size	Colour	Weight (kg)
SS010001	0.9 m x 0.9 m	Black	9.95

## Technical Specifications

<b>Material</b>	Rubber mix, including >50% recycled material
<b>Surface Finish</b>	Textured with holes to allow drainage
<b>Product Height</b>	18 mm
<b>Hole Size</b>	22 mm
<b>Min. Operating Temperature</b>	-20°C
<b>Max. Operating Temperature</b>	+130°C
<b>Resistance to Chemicals</b>	Natural rubber offers limited resistance to chemicals and oils

<b>Environmental Resistance</b>	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
<b>UV Resistance</b>	Yes
<b>Typical Applications</b>	All industrial environments. Areas where swarf is prevalent.
<b>Installation Method</b>	Loose lay interlocking tiles
<b>Cleaning Method</b>	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
<b>Storage and application</b>	Store at room temperature, free from deformations.
<b>Tensile Strength</b>	3 to 3.5 MPa
<b>Notes</b>	Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water.
<b>Slip Tested to</b>	DIN 51130 - R10

## Additional Information



Fatigue Step DIN 51130 Ramp Slip Test

Get in touch | To order FREE samples or arrange a site visit please call +27 (0) 11 452 7961 or email [sales@cobafrica.com](mailto:sales@cobafrica.com)

[www.coba.com/za](http://www.coba.com/za)